



REV.	ECN NO.	MODIFY MATTER	DATE	APPROVED
A		RELEASE TO PRODUCTION		

- NOTES:
- MATERIAL SPECIFICATION:
    - HOUSING: THERMOPLASTIC (UL94V-0)
    - SHELL: COPPER ALLOY & SPC PLATING; NICKEL
    - TERMINAL: COPPER ALLOY
  - ELECTRICAL CHARACTERISTIC:
    - VOLTAGE CURRENT RATING: 1AMP, 30V DC;
    - INSULATION RESISTANCE: 1000MΩ MIN;
    - CONTACT RESISTANCE: 30mΩ MAX;
    - WITHSTANDING VOLTAGE: 500V AC;
  - MECHANICAL:
    - MATING FORCE: 3.5 KG MAX
    - UNMATING FORCE: 1.02 KG MIN.

### EAST-USB2HXPR1R

B: BLACK  
W: White  
1: 铁壳  
2: 铜壳

TOLERANCES UNLESS OTHERWISE SPECIFIED:		DRAWN: CHENLEI		CHECKED: CHENLEI		APPROVED: QINMAIXING	
X	± 0.38	2017/09/10		2017/09/10		2017/09/10	
X.X	± 0.25	2017/09/10		2017/09/10		2017/09/10	
X.XX	± 0.10	2017/09/10		2017/09/10		2017/09/10	
X.XXX	± 1°	2017/09/10		2017/09/10		2017/09/10	
Angle	± 1°	2017/09/10		2017/09/10		2017/09/10	
THESE DRAWING AND SPECIFICATION ARE THE PROPERTY OF Shenzhen Dongfangyue Electronic Co., Ltd. SHALL NOT BE REPRODUCED.							
CUSTOMER COPY		PART NO: EAST-USB2HXPR1R		SCALE: N/A		SHEET: 1:1	
深州市东方御业科技有限公司		USB A/F DIP 90° 加高型鱼叉脚插板加后塞		SCALE: N/A		SHEET: 1:1	
WWW.DFYCONN.COM		TEL: 0755-27155560		SCALE: N/A		SHEET: 1:1	